

F300K Commissioning Case



The Commissioning Case Has the Following Contents.



Compact Flame Scanner F300K has to be ordered seperately



Ext. User Interface FB30-00 must be ordered seperately



Threaded connection FV30-00 with allen key and stud threaded connection



Threaded connection with purging air connector and globe joint FV40-10, demountable. If necessary, purging air connector can be seperated from the globe joint.



Threaded connection adapter Gi 11/4" to Ga 1"



Intermediate adapter M72 on $1^{1}I_{2}^{*}$ inside thread



Power pack with and without LSB modules and network connection



Connection cable on power pack, length 5 m



Remote Software including USB/CAN module



Connection cable USB/CAN module on FSB, length 2m




USB/Connecting cable, length 5 m



FSB Y-adapter to connect to PC Remote Software



Adapter cable COEN Flame Sensor F200K, should COEBN be provided by the customer, lenth 30 cm, must be ordered seperately



Adapter cable F200K/F300K, should F200K be provided by the customer, 30 $\,\mathrm{cm}$



Testing device FFP30



FSB module with connecting cable, length 20 cm

On-site Mechanical Adaption.

Ga 1" provided by the customer



Gi 1" provided by the customer



Ga 1 ¹/₄" provided by the customer



Gi 1 1/2" provided by the customer



Ga 2" provided by the customer



M72 provided by the customer



On-site Electrical Adaption.

Without F200K



With F200K



Spare Parts.

Threaded connection FV30-00 Alu	659S1201
Power pack	7002061-40100ST
Testing device FFP30	659M5000
Connecting cable for power pack	7002060-703ST
FSB Y-adapter	659N0801
Adapter cable F200K/F300K	659N1000
Connecting cable F300K/power pack 5 m	7002061-702ST
USB Cable for Remote Software 5 m	7002061-70200
Connecting cable USB/CAN module 2 m	659N0710
F300K Remote Software, from WIN XP onwards, cable, isolated from voltage, without USB/CAN module	659R9001
USB/CAN-modul	F300K0006
Globe joint FS10-2 with flange, Gi 2"	659E0105
Purge air connection, anodised	6512300-80001
Threaded connection adapter Gi 11/4" on Ga 1"	659E0000

Seperate Parts

C	CEOAEO
Compable Flame Scanner F300K	659A50
Ext. user interface FB30-00	659M2100
Adapter cable COEN Flame sensor on F200K	659N1100
FSB module for 4 analogue inputs	659M3003
FSB module for 4 digital inputs	659M3004
Connecting cable for FSB module 20 cm	



LAMTEC Meß- und Regeltechnik für Feuerungen GmbH & Co. KG

Wiesenstraße 6 D-69190 Walldorf

Telefon: +49 (0) 6227 6052-0 Telefax: +49 (0) 6227 6052-57

info@lamtec.de

www.lamtec.de

